



WORLD TAPES

adhesive and safety solutions

WORLD TAPES S.L.

Avda Touroperador, Bungalow Las Carrozas n. 1, Campo International (Maspalomas)

CP 35100 San Bartolomé de Tirajana, Las Palmas España - info@worldtapes.es - www.worldtapes.es

Technical data sheet

WT-7124 d/s yellow PP tape

Issue date: 05/6/2012

Edition: 1

Authorized:

DIMENSIONS:

Thickness: 0,15 mm (without liner)
Roll widths from: 4 to 1360 mm

SPECIFICATIONS:

Adhesive: open side: Rubber adhesive
closed side: Removable solvent acrylic
Carrier: yellow PP
Liner: d/s siliconised white paper

Peel adhesion: open side: 37 +/- 2 N/25mm
closed side: 3,7 +/- 2 N/25mm
Elongation at break: 600%

APPLICATIONS:

Particularly advised to fix moquette and carpets.

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.