



# WORLD TAPES

adhesive and safety solutions

## WORLD TAPES S.L.

Avda Touroperador, Bungalow Las Carrozas n. 1, Campo International (Maspalomas)

CP 35100 San Bartolomé de Tirajana, Las Palmas España - [info@worldtapes.es](mailto:info@worldtapes.es) - [www.worldtapes.es](http://www.worldtapes.es)

---

### *Technical data sheet*

## **WT-9127 Hi-performance Transfer tape**

*Issue date: 05/6/2012*

---

*Edition: 1*

---

*Authorized:*

---

### **DIMENSIONS:**

**Thickness:** 0,05 mm  
**Roll widths from:** 4 to 1500 mm

### **SPECIFICATIONS:**

**Adhesive:** modified solvent acrylic  
**Carrier:** fiber glass  
**Liner:** d/s siliconised Havana paper 90 gr/m2  
**Peel adhesion:** 20 +/- 2 N/25mm  
**(PSTC 1)**  
**Temperature resistance:** - 30° + 150°C  
**PH Level:** between 7,0 and 8,5

### **APPLICATIONS:**

On paper, cardboard, posters, tissue ,to stick photographs onto albums, etc...  
On version T-927/R (REVERSE) rolls are produce on 1" core on dimensions  
6-9-12-19 mm x 33 or 55 m And to use with our WT-R50 or other kind of dispenser.

---

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.