



WORLD TAPES

adhesive and safety solutions

WORLD TAPES S.L.

Avda Touroperador, Bungalow Las Carrozas n. 1, Campo International (Maspalomas)

CP 35100 San Bartolomé de Tirajana, Las Palmas España - info@worldtapes.es - www.worldtapes.es

Technical data sheet

WT-9179 D/S White PVC tape

Issue date: 05/6/2012

Edition: 1

Authorized:

DIMENSIONS:

Thickness: 0,22 mm
Roll widths from: 4 a 1250 mm

SPECIFICATIONS:

Adhesive: modified solvent acrylic
Carrier: White PVC
Liner: d/s siliconised yellow paper 110 my
Peel adhesion: +/- 2 N/25mm
(PSTC 1)
Temperature resistance: - 30° + 80°C

APPLICATIONS:

For a wide range of applications on metal or plastic plates. Particularly advised on profiles.
Available in spool wound roll form in different widths 4 to 19 mm lengths.

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.